Certified Translation from German into English



Safety Data Sheet according to VO 1907/2006/EC

Product name: iglidur® J260 Status: 9 January 2014 Page: 1/3

1 Description of the material / product and company

Description of the material or product: iglidur® J260

Use of the material or product: Moulded plastic parts

Description of the company: igus® GmbH

Spicher Str. 1a D-51147 Cologne

Telephone: 02203/9649-0 Fax: 02203/9649-222

Emergency call (Poison Information Centre North): 0551/19240

2. Possible risks

Noxious gases or dusts may form in the event of a fire and during machining, see Point 10. The product will burn when exposed to fire. Please call the Poison Information Centre North (see Point 1) in emergencies. The product does not require labelling.

The thermal decomposition products of fluorinated polymers can cause polymer fume fever with flulike symptoms in humans, especially following smoking of contaminated tobacco products.

3 Composition / information about components

Product based on a thermoplastic polymer mixture with additives and fillers.

4. First-aid measures

Inhalation: After inhaling decomposition products, move affected persons into the open air and let them rest. Call a medical doctor in case of complaints.

Skin contact: Mechanical effects may lead to irritation or injuries.

Eye contact: Mechanical effects may lead to irritation or injuries. Rinse several minutes with clean water or eye solution while keeping the eyelids pulled open. Seek immediate medical attention if complaints persist.

Ingestion: Call a medical doctor and show this safety data sheet. If victim is unconscious, never administer water.

5 Fire-fighting measures

Suitable fire-extinguishing agents: Sprayed water jet (mist), foam, fire extinguishing powder, carbon dioxide.

Unsuitable fire-extinguishing agents: Water with full jet.

Use a breathing apparatus that is independent of the environmental air. Dangerous combustion gases; see Point 10. Under certain fire conditions, traces of other toxic substances cannot be ruled out. The emergence of further decomposition and oxidation products depends on the fire conditions. In the case of fire a dense, black smoke will occur which can contain dangerous combustion products.

Adapt fire-fighting measures to surrounding fire. Do not inhale fumes.

Dispose of contaminated fire fighting water and fire residues in accordance with official regulations.

Compiled:	DrIng. Ralf Selzer /	Approved:	Peter Spanier	Amended:		F-2-0059-B	
	9.1.2014					Т-2-0039-В	

Certified Translation from German into English



Product name: iglidur® J260 Status: 9 January 2014 Page: 2/3

6 Measures after unintentional release

Personal precautions: Remove mechanically to prevent risk of slipping.

Environmental protection measures: Do not allow to penetrate soil, water or canalisation.

7 Handling and storage

Notes for safe handling: Machining requires good ventilation or extraction systems at the processing machines.

General hygiene measures for the use of chemicals must be adhered to. Eating, drinking and smoking in the work room is prohibited. Do not store food. Avoid dust formation.

Special storage conditions: Store in a cool and dry place. Do not store in passageways or staircases. Keep clear from sources of ignition. The product is combustible. Do not store together with strong acids and oxidizing agents.

Take measures against electrostatic charging.

Storage class according to VCI: (11) Flammable solids.

8 Limitation and monitoring of exposure / personal protective equipment

No personal protective measures are required during appropriate use and application. Wash hands after use, in particular before eating, drinking or smoking.

9 Physical and chemical properties

Commercial form: Moulded plastic part / solid

Colour: Yellow

Flash point:

Ignition temperature:

Self-igniting solid:

Fire-enhancing properties:

Density:

Solubility in water:

Not determined

Not determined

Not determined

Not determined

Insoluble

10 Stability and reactivity

No decomposition during appropriate use. To avoid thermal decomposition do not overheat.

The thermal decomposition of the product starts at 330°C.

Hazardous fumes: Carbon monoxide, carbon dioxide, nitrogen oxide, phenol, aldehyde, hydrocyanic acid, hydrogen fluoride, carbonyl fluoride, perfluoroisobutylene, fluorinated hydrocarbons, as well as toxic fumes, gases or particles.

11 Toxicological information

The product does, to the best of our knowledge, not have any noxious effects when it is appropriately handled and used.

Compiled:	DrIng. Ralf Selzer /	Approved:	Peter Spanier	Amended:		F-2-0059-B
	9.1.2014					1 2 0000 B

Certified Translation from German into English



Product name: iglidur® J260 Status: 9 January 2014 Page: 3/3

Do not heat product to temperatures above 140°C.

Notes for safe handling: Machining requires good ventilation or extraction systems at the processing machines.

12 Environmental relevant information

Migration behaviour and behaviour in the ecosystem: The product is a solid polymer that is insoluble in water and is not expected to have any disadvantageous effects on plants, animals or micro-organisms. It should nevertheless not be allowed to penetrate into the ground water, bodies of water or the drainage system.

Persistence and degradation: The substance is not biodegradable.

Behaviour in waste water treatment plants: Effects at the biological cleaning stage are not to be expected.

13 Disposal information

The product can be incinerated in an approved plant in compliance with technical guidelines or stored together with domestic waste in an appropriate landfill site.

Hydrogen fluoride must be removed by flue gas scrubbing.

Waste name: Fluorine-containing plastic waste.

EC Waste key number: The waste key depends on the intended purpose of the product.

14 Transport information

Not deemed to be hazardous goods according to the transport regulations (GGVS/ADR, GGVE/RID, GGVBinSch/ADNR, GGVSee/IMDG Code, ICAO-Ti/IATA-DGR). Sending by mail is permitted.

15 Information concerning legal regulations

No compulsory marking according to EU Directives.

Water hazard class: nwg - not hazardous to water

16 Other information

The information provided above is based on the current state of our knowledge and does not guarantee any properties. The receiver is responsible for compliance with existing laws and regulations.

This document is not subject to a change service.

This is to certify that the above translation from German into English is complete and correct.

Königswinter, 17.1.2014

Sabine Bartsch Sworn Translator for the Higher Regional Court of Cologne/Germany

Compiled:	DrIng. Ralf Selzer /	Approved:	Peter Spanier	Amended:		F-2-0059-B
-	9.1.2014		•			1 -2-0039-D