



Silver Age Sci. & Tech. Co., Ltd.

<http://www.silver-3d.com/>

Karing <karing@silverage.cn>

| Filament | Special Properties | Uses | Strength | Flexibility | Durability | Print Skills | Print Temperature | Bed Temperature |
|--------------------|---|--|----------|-------------|------------|--------------|-------------------|-------------------|
| PLA | Easy to Print, Biodegradable | Consumer Products | ★★ | ★ | ★★ | ★ | 195-210°C | Non-heat/50-60 °C |
| ABS | Durable, Impact Resistant | Functional Parts | ★★ | ★★ | ★★★★ | ★★ | 220-260°C | 100-110°C |
| PVA | Disolvable, Water Soluble, Biodegradable, Oil Resistant | PLA/ABS Dual Extrusion, Support Structures | ★★★★ | ★ | ★★ | ★ | 190-210°C | Non-heat/60-80 °C |
| WOOD PLA | Wood Finish | Home Decor | ★★ | ★★ | ★★ | ★★ | 190-220°C | Non-heat/50-60 °C |
| Flexible, TPE, TPU | Extremely Flexible, Rubber-Like | Elastic Parts, Wearables | ★ | ★★★★ | ★★ | ★★★★ | 210-230°C | Non-heat |
| PA | Strong, Flexible, Durable | All-Rounder | ★★★★ | ★★★★ | ★★★★ | ★★ | 240-260°C | 100-110°C |
| PC | Rigid, Durable, Impact Resistant, Resilient, Deflecting | Functional Parts | ★★ | ★ | ★★★★ | ★★★★ | 240-260°C | 100-110°C |
| PC+ | Strongest, Flexible, Durable, Transparent, Heat Resistant | Functional Parts | ★★★★ | ★★★★ | ★★★★ | ★★ | 220-260°C | 90-110°C |
| HIPS | Disolvable, Biodegradable | ABS Dual Extrusion, Support Structures | ★ | ★★ | ★★★★ | ★★ | 220-260°C | 100-110°C |
| Metallic Color | Easy to Print, Biodegradable | Consumer Products | ★★ | ★ | ★★★★ | ★★★★ | 185-210°C | Non-heat/50-60 °C |
| PETG | Flexible, Durable | All-Rounder | ★★ | ★★★★ | ★★★★ | ★★ | 230-260°C | 100-110°C |

Silver 3D
Since 2008
AUTHORITIES DETECTION
THE LISTED COMPANY SECURITY
STEEL BRONZE PLA FILAMENT
 • No plug
 • No bubble
 • Not warp
 • Stable quality
silver3d.en.alibaba.com

Color can be customized

AUTHORITIES DETECTION
THE LISTED COMPANY SECURITY
WOOD FILAMENT
 • Security
 • High precision
 • Can be polished