According to EU Directive 1907/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015

1.0

1. Identification of the substance/preparation and of the company

1.1 Trade name: E3D Scaffold

1.2 Use of the product: PVA based polymer blend, enhanced for the extrusion of 3Dprinter filaments

1.3 Supplier: E3D Online

Unit 56, Monument Bus Pk

Chalgrove Oxfordshire OX44 7RW

UK

Phone: +44(0)1865 890 541

Emergency phone number: +44(0)1865 890 541

2. Hazards identification

2.1 Classification of the substance or mixture classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.3 Other hazards

Skin sensitization material (Category 1) is contained less than 0.1%.

3. Composition/information on ingredients

3.1 Mixtures

Hazardous components

	•		
Chemical	CAS-No.	Classification	Concentration
Name	EC-No.	(1272/2008/EC)	[%]
	Registration		
	number		
methanol	67-56-1	Flam. Liq. 2; H225	< 1
	200-659-6	Acute Tox. 3; H301	
		Acute Tox. 3; H331	
		Acute Tox. 3; H311	
		STOT SE 1; H370	

For the full text of the H-Statements mentioned in this Section, see Section 16.

Version:

According to EU Directive 1907/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015 Version:

1.0

4. First aid measures

4.1 Description of first aid measures

General advice: If you feel unwell, seek medical advice (show the label where possible).

Never give anything by mouth to an unconscious person. Take

off contaminated clothing and shoes mmediately.

If inhaled: If breathed in, move person into fresh air.

In case of skin contact: If on skin, rinse well with water. If skin irritation persists, call a physician. In case of eye contact: If easy to do, remove contact lens, if worn. In the case of contact with

eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed: Rinse mouth with water. Induce vomiting immediately and call a physician.

If a person vomits when lying on his back, place him in the recovery

position.

4.2 Most important symptoms and effects, both acute and delayed

no data available

4.3 Indication of any immediate medical attention and special treatment needed

no data available

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray jet, Dry chemical Unsuitable extinguishing media: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting: Do not use a solid water stream as it may scatter and

spread fire. Exposure to decomposition products may be a

hazard to health.

5.3 Advice for firefighters

Special protective equipment for firefighters: Wear self-contained breathing apparatus for

firefighting if necessary. Use personal protective

equipment.

Further information: Standard procedure for chemical fires. Use

extinguishing measures that are appropriate to

local circumstances and the surrounding

environment. In the event of fire and/or explosion

do not breathe fumes.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. Avoid dust formation. Avoid breathing dust. Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

no data available

6.3 Methods and materials for containment and cleaning up

Use mechanical handling equipment. Keep in suitable, closed containers for disposal. Clean contaminated surface thoroughly.

6.4 Reference to other sections

see chapter: 7, 8, 11, 12 and 13

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling: For personal protection see section 8. Avoid

creating dust. Do not breathe dust. Avoid contact

with skin and eyes.

Advice on protection against fire and explosion: Normal measures for preventive fire protection.

Dust explosion class: No data available.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers: Keep containers tightly closed in a dry, cool and

ventilated place.

Further information on storage conditions: Protect from moisture.

Advice on common storage: Keep away from oxidising agents and strongly

acid or alkaline materials. Keep away from oxidising agents at

or alkaline materials. Keep away from food, drink

and animal feedingstuffs.

Storage temperature: <= 40 °C

Other data: No decomposition if stored and applied as

directed.

7.3 Specific end use(s)

no data available

page 3/10

According to EU Directive 1907/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015 Version:

1.0

8. Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Control parameters	Basis	Update
methanol	67-56-1	TWA: 266 mg/m ³ , 200 ppm Sk, STEL: 333 mg/m ³ , 250 ppm Sk,	GB EH40	2005-04-06
Components	CAS-No.	Control parameters	Basis	Update
methanol	67-56-1	TWA: 260 mg/m ³ , 200 ppm skin,	2006/15/EC	2006-02-09

Other information on limit values: see chapter 16

8.2 Exposure controls

Engineering measures

Provide adequate ventilation.

Personal protective equipment

Respiratory protection: In the case of dust or aerosol formation use respirator with

an approved filter. Half mask with a particle filter P2 (EN

143).

Hand protection:

Eye protection:

Skin and body protection:

Rubber gloves

Goggles

Apron

Hygiene measures: Handle in accordance with good industrial hygiene and

safety practice. General industrial hygiene practice. Do not breathe dust. Avoid contact with skin, eyes and clothing. When using do not eat, drink or smoke. Wash hands before breaks and at the end of workday. Wash

contaminated clothing before re-use.

Environmental exposure controls

no data available

page 4/10

Safety Data Sheet

According to EU Directive 1907/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015 Version:

1.0

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: pellets

Colour: white, light yellow Odour: slight vinegar-like Odour Threshold: no data available

Flash point: > 200 °C, Method: Seta closed cup

Ignition temperature: 520 °C

Thermal decomposition: >= 200 °C

Lower explosion limit: 35 g/m3

Upper explosion limit:

Explosive properties:

Flammability:

Oxidizing properties:

Auto-ignition temperature:

Burning number:

Molecular Weight:

no data available
no data available
no data available

pH: 5.0 – 7.0
Concentration: 100.00 g/L
Melting point/range: 150 - 230 °C
Vapour pressure: no data available
Density: 1.19 – 1.31 g/cm3
Bulk density: no data available

Water solubility: insoluble

Partition coefficient: n- octanol/water: no data available

Solubility in other solvents:

insoluble Medium: Acetone

Insoluble

Medium: Alcohol

insoluble

Medium: n-hexane

Insoluble

Medium: toluene

soluble

Medium: Dimethylformamide

soluble

Medium: Dimethyl sulfoxide

Viscosity, dynamic: no data available Viscosity, kinematic: no data available Flow time: no data available Impact Sensitivity: no data available Relative vapour density: no data available no data available Surface tension: no data available Evaporation rate: Minimum ignition energy: no data available Acid number: no data available Refraction index: no data available Miscibility in water: no data available Solvent separation test: no data available

page 5/10

Safety Data Sheet

According to EU Directive 1907/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015 Version:

1.0

9.2 Other information

None known.

10. Stability

10.1 Reactivity

no data available.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Stability: No decomposition if stored and applied as directed. Dust can form an

explosive mixture in air.

10.4 Conditions to avoid

no data available

10.5 Incompatible materials

Materials to avoid: Oxidizing agents, Acids, Bases

10.6 Hazardous decomposition products

Hazardous decomposition products: Build-up of dangerous/toxic fumes possible in cases of

fire/high temperature.

11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity: LD50 Oral : > 2,000 mg/kg

Acute inhalation toxicity: Acute toxicity estimate : > 20 mg/L

Test atmosphere: vapour Exposure time: 4 h

Method: Calculation method

Acute dermal toxicity: Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

page 6/10

According to EU Directive 1907/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015 Version:

1.0

Acute toxicity (other routes of administration)

no data available

Skin corrosion/irritation

methanol: Species: rabbit

No skin irritation

Serious eye damage/eye irritation

methanol: Species: rabbit

No eye irritation

Respiratory or skin sensitization

Sensitisation:

methanol: Test Method: Maximisation

Test Species: guinea pig

Result: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Genotoxicity in vitro:

Genotoxicity in vivo:

no data available
no data available

Carcinogenicity

Remarks:

Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Reproductive toxicity: no data available

Teratogenicity: no data available

STOT - single exposure

methanol: Causes damage to organs.

STOT - repeated exposure

no data available

Aspiration hazard

Aspiration toxicity: no data available

Neurological effects: no data available

Toxicology Assessment

Toxicology, Metabolism, Distribution: no data available.

Acute effects: no data available page 7/10

According to EU Directive 1907/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015 Version:

1.0

12. Ecological information

12.1 **Toxicity**

Toxicity to fish: (Oncorhynchus mykiss (rainbow trout)): >

100 mg/L Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates: (Daphnia magna (Water flea)): > 100 Exposure time: 48 h

mg/L

Toxicity to algae: (algae): > 100 mg/L

Toxicity to bacteria

methanol: IC50: > 1,000 mg/L Exposure time: 3 h

> Test Method: Respiration inhibition of activated sludge Method: OECD Test

Guideline 209

Toxicity to fish (Chronic toxicity):

methanol: NOEC: 7,900 mg/L

Exposure time: 200 h

Species: Oryzias latipes (Orange-red

killifish)

12.2 Persistence and degradability

Biodegradability

methanol: Result: Readily biodegradable.

12.3 **Bioaccumulative potential**

Bioaccumulation

methanol: Species: Cyprinus carpio (Carp)

Concentration: 5 mg/L Bioconcentration

factor (BCF): 1 - 4.5

12.4 Mobility in soil

no data available

Results of PBT and vPvB assessment 12.5

no data available

12.6 Other adverse effects

Additional ecological information: The product should not be allowed to

enter drains, water courses or the soil.

page 8/10

According to EU Directive 1907/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015 Version:

1.0

13. Disposal considerations

13.1 Waste treatment methods

Advice on disposal and packaging: Disposal: In accordance with local and national

regulations. Do not dispose of together with household waste. Waste codes should be assigned by the user based on the application for which the product was used.

14. Transport information

ADR

Not dangerous goods

RID

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Special precautions for user

see chapter: 6, 7 and 8

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC: 0.5 %

VOC content less water: 6.55 g/L

Directive 96/82/EC: Update: 2003

Directive 96/82/EC does not apply

Further information: Reserved for industrial and professional use.

15.2 Chemical Safety Assessment

no data available

Page 9/10

Safety Data Sheet

According	to Fl	J Directive	1907	/2006

Product name: E3D Scaffold

Date of issue: 12 October 2015 Version:

1.0

16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapour

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

Other information

Sk Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

skin Identifies the possibility of significant uptake through the skin

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

page 10/10